

Data Sheet

Mixing / Magnetic Stirrers



Midi MR 1 digital IKAMAG®

Powerful magnetic stirrer without heating.

- Flat, sturdy stainless steel casing
- Non-locking motor
- Infinitely variable speed
- Digital LED speed display
- Timer (0 - 56 min) or continuous operation
- For stirring quantities up to 50 liters (H₂O)

Accessories: TRIKA® 40 Magnetic stirring bar, TRIKA® 25 Magnetic stirring bar, RSE Stirring bar remover, IKAFLON® 30 Magnetic stirring bar, IKAFLON® 80 Magnetic stirring bar, H 11 Mains cable CH plug, IKAFLON® 50 Magnetic stirring bar, H 11 Mains cable Euro plug, H 11 Mains cable USA plug, H 11 Mains cable UK plug, IKAFLON® 40 Magnetic stirring bar

Technical Data

Number of stirring positions	1
Stirring quantity max. per stirring position (H ₂ O) [l]	50
Motor rating input [W]	70
Motor rating output [W]	19
Speed display	LCD
Speed range [1/min]	0 - 1000
Stirring bar length max. [mm]	80
Set-up plate material	stainless steel 1.4301
Set-up plate dimensions [mm]	350 x 350
Dimensions (W x H x D) [mm]	360 x 110 x 430
Weight [kg]	10.7
Permissible ambient temperature [°C]	5 - 40
Permissible relative moisture [%]	80
Protection class according to DIN EN 60529	IP 21
Voltage [V]	230 / 100 - 120
Frequency [Hz]	50/60
Power input [W]	70
Ident. No.	2621900